



14	EYE BOLT	M.S.
13	FLAME PROOF GLAND	STD.
12	O RING	NEOPRENE
11	TERMINAL BOX	AL. LM-6
10	HEX. SOCKET HEAD CAP SCREW	M.S.
09	CONNECTION STUD FIXING PLATE	AL. LM-6
08	HEX. BOLT (FOR EARTHING)	BRASS
07	CONNECTION STUD	STD.
06	ENCLOSURE HOUSING	AL. LM-6
05	A.C./ D.C. DISC BRAKE	STD.
04	HEX. SOCKET HEAD CAP SCREW	M.S.
03	ENCLOSURE FLANGE	AL. LM-6
02	O RING	NEOPRENE
01	BRASS BUSH	BRASS
SR NO	DESCRIPTION	MATERIAL

BRAKE MODEL	TORQUE KG.M	PHASE	VOLTAGE
DAT-190	2.5	3	415 V.AC
DAT-190X	4.5	3	415 V.AC
DAT-235	4.1	3	415 V.AC
DAT-235X	6.0	3	415 V.AC
SLDC - 170	5.0	-	6V. DC TO 220V. DC
SLDC - 195	8.0	-	6V. DC TO 220V. DC
SLDC - 235	14.0	-	6V. DC TO 220V. DC

FLAME-PROOF / WEATHER-PROOF ENCLOSURE CONSTRUCTED IN ACCORDANCE WITH THE PROVISIONS AS SPECIFIED IN IS/IEC 60079-1 : 2007, SUITABLE FOR GAS GROUPS IIB AND ZONE I & II ATMOSPHERE

ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED. SIZE : MEDIUM

  **FLAME PROOF / WEATHER PROOF ENCLOSURE FOR AC AND DC DISC TYPE BRAKE DAT & SLDC SERIES**

Drg. No : PIMC/FP/SM/07

PETHE INDUSTRIAL MKTG. CO. PVT. LTD.
 69,S.K. BHLE ROAD, DAGDIWADI, DADAR (W) MUMBAI - 400 028
 TEL : 022-2422 3976 / 2422 0923 TELEFAX : 022-2422 8998